





Cap.	WV	100VDC				250VDC				400VDC				630VDC			
		H	W	T	P	H	W	T	P	H	W	T	P	H	W	T	P
0.001		10.5	5.8	3.3	3.0	10.0	6.0	3.5	3.5	10.0	6.0	3.5	3.5	10.0	7.0	3.5	4.0
0.0015		10.5	5.8	3.3	3.0	10.0	6.0	3.5	3.5	10.0	6.0	3.5	3.5	10.0	7.0	3.5	4.0
0.0022		10.5	5.8	3.3	3.0	10.0	6.0	3.5	3.5	10.0	6.0	3.5	3.5	10.0	7.0	4.0	4.0
0.0033		10.5	5.8	3.3	3.0	10.0	6.0	3.5	3.5	10.0	6.0	3.5	3.5	12.0	7.0	4.0	4.0
0.0047		10.5	6.5	3.5	3.0	10.0	7.0	4.0	4.0	10.0	7.0	4.0	4.0	12.0	8.0	4.0	5.0
0.0056		10.5	6.5	3.5	3.0	10.0	7.0	4.0	4.0	10.0	7.0	4.0	4.0	12.0	8.5	4.0	5.0
0.0068		10.5	6.5	3.5	3.0	10.0	7.0	4.0	4.0	10.0	7.0	4.0	4.0	12.0	8.5	4.5	5.0
0.0082		10.5	6.5	4.0	3.0	10.0	7.0	4.0	4.0	10.0	7.0	4.0	4.0	12.0	9.0	4.5	5.0
0.01		10.5	6.5	4.0	3.0	10.0	7.0	4.0	4.5	10.0	7.0	4.0	4.5	12.0	9.0	4.5	5.0
0.015		10.5	7.5	4.0	4.0	11.0	7.0	4.0	5.0	12.0	8.0	5.0	5.0	13.0	9.0	5.0	5.0
0.022		10.5	7.8	4.5	4.0	11.0	7.5	4.0	5.0	12.0	8.5	5.0	6.0	13.0	9.0	5.0	6.0
0.027		12.0	7.8	4.5	5.0												
0.033		12.0	8.0	4.5	5.0	12.0	8.0	4.5	6.0	13.0	9.0	5.0	6.5	13.0	9.0	5.0	6.5
0.047		12.5	9.3	5.0	5.0	12.0	9.0	5.0	6.0	13.0	11.0	6.0	7.0	13.0	11.0	6.0	7.0
0.056		12.5	9.7	5.0	5.0	12.0	9.0	5.5	6.0	13.0	11.5	6.5	7.0	13.0	11.5	6.5	7.0
0.068		12.5	10	5.5	5.5	12.0	10.0	6.0	6.0	13.0	12.0	7.0	7.0	13.0	12.0	7.0	7.0
0.082		12.5	10.5	6.0	6.0	13.0	11.0	6.5	7.0	13.0	13.0	8.0	7.5	13.0	13.0	8.0	7.5
0.1		13.0	11.5	6.5	6.5	13.0	11.0	7.0	7.0	14.0	14.0	9.0	7.5	15.0	14.0	9.0	7.5
0.12		13.0	12.0	7.0	7.0												
0.15		15.0	12.0	7.0	7.0												
0.22		16.0	12.0	8.0	7.5												
0.27		16.0	12.5	8.5	8.5												
0.33		17.0	13.5	8.5	8.5												
0.39		17.5	14.0	9.0	9.0												
0.47		18.0	15.0	10.0	10.0												